



2277 E. North Street
Kokomo, IN 46901

ph: 765.456.3957
fax: 765.456.3960

www.CoanRacing.com

COA-12829 ALUMINUM DIRECT DRUM

Proper band installation and adjustment is crucial with Aluminum drums. Soak band in transmissiion fluid for 1 hour prior to installation. (**DO NOT** use bands with Kevlar lining.) Tighten band to 72 inch pounds. Then back out four and one half turns. If engine flares on gear change, tighten band $\frac{1}{4}$ turn until flaring is eliminated.

If you have any questions regarding the proper installation and/or operation of a Coan Racing product, please call (765) 456-3957. You may also fax us at (765) 456-3960, or e-mail at coan@coanracing.com.

Warranty

Coan Engineering offers a limited warranty covering all new products for ninety days and all repair service for thirty days from the original date of purchase to be free from flaws in material and craftsmanship. The warranty is non-transferable. Under no circumstances will Coan Engineering extend its warranty to products, new or repaired, which have been abused, misused, or incorrectly installed. Disassembly of any product by means other than a Coan Engineering technician will void any potential warranty. All warranty claims must be accompanied by the original invoice and are subject to the approval of Coan Engineering.

The above stated warranty **does not include** any shipping charges or labor charges for installation or removal of any Coan Racing product.

Liability

In no manner, neither written nor implied, does Coan Engineering accept liability for consequential or incidental damages to person or property resulting from the use or misuse of its products. Product failure occurring within the stipulations of the warranty policy will be dealt with explicitly under those particular guidelines.

